



标准色: 黄色

材料: PA 6

**更高配合度。**

适用于DIN 3852-1、DIN ISO 6149-1的内螺纹。

**更强密封性。**

环向密封唇(无分模特征)和O型圈防止液体渗透或泄漏,具体取决于应用。

**更坚固。**

由优质抗冲击聚酰胺制成。

**更优质。**

与GPN 735的特点相同,但带有额外O型圈,用于满足更严格的密封性要求(例如未加工的密封表面、高加工温度、长加工时间及更高部件内压)。

产品名称	螺纹 K	尺寸			扳手宽度 (开口宽度)	订单编号
		A	H	(M)		
GPN 737 M 8 × 1	M 8 × 1	12.2	8	15	6	737 0810 0000
GPN 737 M 10 × 1	M 10 × 1	14.2	8	15	7	737 1010 0000
GPN 737 M 12 × 1.5	M 12 × 1.5	17.2	11	18	10	737 1215 0000
GPN 737 M 14 × 1.5	M 14 × 1.5	19.2	11	19	10	737 1415 0000
GPN 737 M 16 × 1.5	M 16 × 1.5	22	11	21	13	737 1615 0000
GPN 737 M 18 × 1.5	M 18 × 1.5	24	11	21	13	737 1815 0000
GPN 737 M 20 × 1.5	M 20 × 1.5	26	11	21	15	737 2015 0000
GPN 737 M 22 × 1.5	M 22 × 1.5	27.2	11	21	15	737 2215 0000
GPN 737 M 24 × 1.5	M 24 × 1.5	31.5	12	22	15	737 2415 0000
GPN 737 M 26 × 1.5	M 26 × 1.5	32	13.5	23.5	19	737 2615 0000
GPN 737 M 27 × 2	M 27 × 2	32.3	11	21	19	737 2720 0000
GPN 737 M 33 × 2	M 33 × 2	40.4	13.5	23.5	24	737 3320 0000
GPN 737 M 42 × 2	M 42 × 2	50	13.5	24.5	24	737 4220 0000
GPN 737 M 48 × 2	M 48 × 2	55.4	13.5	24.5	30	737 4820 0000
GPN 737 M 60 × 2	M 60 × 2	68.5	13.5	24.5	30	737 6020 0000
GPN 737 G 1	G 1	40	11.5	21.5	24	737 0662 0000
GPN 737 G 1 1/2	G 1 1/2	55.4	11.5	22.5	30	737 0664 0000
GPN 737 G 1 1/4	G 1 1/4	50.4	11.5	22.5	24	737 0663 0000
GPN 737 G 1/2	G 1/2	27.2	9.5	19.5	15	737 0660 0000
GPN 737 G 1/4	G 1/4	19.2	7.5	15	10	737 0658 0000
GPN 737 G 3/4	G 3/4	32.3	9.5	19.5	19	737 0661 0000
GPN 737 G 3/8	G 3/8	22.2	7.5	17.5	13	737 0659 0000
GPN 737 9/16 - 18 UNF	9/16 - 18 UNF	17.8	11	18	10	737 2442 0000

尺寸单位: 毫米

产品材料、颜色、图纸和用途信息,请参阅第124/125页。

刻痕与GPN 735标准系列相同。

您还可能对下列产品感兴趣: **GPN 551, GPN 700, GPN 735****更快捷。** 带BIT-73X

BIT-73X装配工具使GPN 730、735、736、737和738标准系列所有尺寸密封塞的安装更加便捷。

更多信息,请参阅第109页。